



Moving Head Beam Light

TL-SL112



Feature

- * Optics: high-precision glass optical lens (6-layer coating), multi-level optical lens group electronic focusing, linear magnification function.
- * Color wheel: 13 color gels + 1 white light, two-way rainbow effect, adjustable speed, flexible positioning function.
- * Gobo system: 1 rotatable gobo wheel: 9 gobos + white circle, with pattern dithering and pattern flexible positioning function, pattern outer diameter: 15mm, 1 fixed gobo wheel: 17 fixed gobos + 1 white light, one-way flowing effect, adjustable speed, flexible positioning function.
- * Effect gobo wheel: flame effect, water effect.
- * 4 prisms: rotating octagonal prism + 6 row lens, rotating hexadecagon prism + honeycomb prism, support two-way rotation, superimposition, and adjustable speed.
- * Strobe: double-chip strobe 0.5-13 times/sec, support synchronous, asynchronous and random strobe modes, and adjustable speed.
- * Atomization: 1 independent atomization effect, the light spot is soft and natural.
- * Scanning range: X-axis 630°/3.8 S, Y-axis 270°/2.0 S, accurate scanning and positioning.
- * Display interface: a widescreen 2.8-inch LCD interface in Chinese and English, with rechargeable battery, you can enter the menu to set the address code and make other settings without powering on; the menu hierarchical structure, friendly graphical interface, general operations including operation gestures such as click, double-click, and slide.
- * Intelligent heat dissipation: using wind direction drainage and temperature intelligent monitoring technology, according to the temperature of different positions of the lamp, the cooling fans in different parts of the lamp are automatically driven to effectively cool the lamp components.
- * Gyroscope: enable the gyroscope function, and the Y-axis is automatically compensated and calibrated; autofocus: 3-25.5 meters autofocus.

Specification

Model	TL-SL112
Input voltage	AC110V-240V 50/60Hz, 480W
Ballast	Electronic ballast
Light source	PHILIPS 380
Average lifespan	2000H
Color temperature	7800K
Beam angle	2.5°~42°
Control mode	DMX512 protocol, support RDM protocol and program online update function; support Art-net Ethernet data interface (DMX wireless function optional)
Channel	18/22 channels
Fixture material	High temperature resistant plastic
Protection class	Ip20
Fixture size (L×W×H)	390×275×630mm
Package size (L×W×H)	515×480×640mm
Net weight	20kg
Gross weight	23.5kg