



# LED Flood Light

## TL-LT691



### Feature

- \* Color: 7 color panels + white light, two-way stepless rotation, magnet positioning, color index, half-color and other functions.
- \* Cutting panel: professional independent cutting module, cut graphics in eight directions, independent aperture mode, adjustable graphics size.
- \* Function: a dynamic effect wheel, two-way stepless rotation.
- \* Prism: optional triangular prism, rectangular prism, four-row lens, etc.
- \* Atomization, 10%-100%.
- \* Light spot changes, high-speed electric linear zoom.
- \* Dimming: 0-100% linear adjustment.
- \* DMX512 port program update, convenient and fast software update via DMX data cable.
- \* Over-temperature protection function: built-in NTC temperature control function, when the LED is overheated, the output power of the LED is intelligently reduced.
- \* LCD blue screen can display the fixture usage time, software version number, etc.

### Specification

<b>Input voltage</b>	AC 110-240V 50/60Hz, 800W
<b>Light source</b>	1 650W white light LED OSRAM chip
<b>Average lifespan</b>	50000H
<b>Color temperature</b>	7500K
<b>Beam angle</b>	5°-50° linear zoom
<b>Control mode</b>	Comply with the international standard DMX512 signal control protocol, 3-core (optional 5-core) DMX512 signal interface; master-slave synchronous control mode, support RDM protocol and program online update function
<b>Operation mode</b>	DMX mode, user program mode, built-in program mode
<b>Channel</b>	16 channels
<b>Fixture material</b>	High temperature resistant aluminum alloy + high temperature resistant / UV resistant engineering plastic + copper tube radiator + 1 waterproof fan to assist heat dissipation
<b>Protection class</b>	IP67
<b>Working temperature</b>	-20°C~45 °C
<b>Fixture size</b>	541mm*346mm*267mm
<b>Package size</b>	405*355*690mm
<b>Gross weight</b>	28.1KG
<b>Net weight</b>	26KG