



# LED Flood Light

## TL-LT611



### Feature:

- \* Strobe: independent electronic strobe 1-25Hz, support random strobe, pulse strobe, synchronous and asynchronous strobe, single color and mixed color temperature strobe.
- \* Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.
- \* Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- \* LCD menu: invoke various scenes, built-in programs can be directly invoked and executed.
- \* Fixture connection: three-core signal line IN/OUT and power line IN/OUT.
- \* Cast aluminum housing, high light efficiency, uniform light mixing, stable performance; equipped with 1m hand in hand power supply and signal line of 1 in and 1 out; 1024-level ultra-high grayscale dimming is softer.

### Specifications:

Model	TL-LT611
Input voltage	AC 110-240V 50/60Hz, 360W
Light source	108×3W LED(R27G27B27W27))
Average lifespan	50000H
Color temperature	3200K~7200K linear adjustment
Beam angle	25°(8/15/45/60°optional)
Control mode	Multiple voice control, DMX512, built-in program self-propelled, master-slave connection mode
Channel	3/7 channels
Fixture material	Cast aluminum housing
Protection level	Fireproof V-1, protection IP65
Fixture size (L×W×H)	715*310*340mm
Net weight	18.5kg
Working temperature	-20°C~45 °C