



LED Flood Light

TL-LT681



Feature

- * Color: one 9+1 fixed color wheel, two-way stepless rotation, magnet positioning, color index, half color and other functions.
- * Function: one 14+1 fixed gobo wheel, independent rotation and two-way stepless rotation.
- * Focusing: electric focusing.
- * Dimming: 0-100% linear dimming.
- * Strobe: electronic strobe, 0-25 times/sec (built-in pulse strobe effect).
- * Display interface: LCD blue screen.
- * Software update: DMX512 port program update, convenient and fast software upgrade through DMX data cable.
- * Over-temperature protection function: built-in NTC temperature control function, when the LED is overheated, the output power of the LED will be intelligently reduced.
- * The screen can display the lamp usage time, software version number, reverse subtitle display, etc.

Specification

Model	TL-LT681
Input voltage	AC110V-240V 50/60Hz, 110W
Light source	80W White LED Optical Module
Average lifespan	20000H
Color temperature	5200K
Beam angle	2.5°
Control mode	Comply with the international standard DMX512 signal control protocol, 3-pin (optional 5-pin) DMX512 signal interface, master-slave synchronous control mode
Operation mode	DMX mode, user program mode, built-in program mode
Channel	7 channels
Fixture material	High-strength die-casting aluminum alloy, copper tube radiator
Protection class	Ip67
Fixture size (L×W×H)	230×180×420mm
Package size (L×W×H)	275×255×500mm
Net weight	8.9kg
Gross weight	9.5kg