



LED Wall Washer

TL-LT622



Feature:

- * Strobe: independent electronic strobe 1-25Hz, support random strobe, pulse strobe, synchronous and asynchronous strobe, single color and mixed color temperature strobe.
- * Color mixing: RGBW (red, green, blue and white) linear color mixing, 16.7 million colors (0-100% saturation adjustment), and built-in macro function.
- * Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- * LCD menu: invoke various scenes, built-in programs can be directly invoked and executed.
- * Fixture connection: three-core signal line IN/OUT and power line IN/OUT.
- * Cast aluminum housing, high light efficiency, uniform light mixing, stable performance; equipped with 1m hand in hand power line and signal line of 1 in and 1 out; 1024-level ultra-high grayscale dimming is softer.
- * Voice control sensitivity: 65-130dB.

Specifications:

Model	TL-LT622
Input voltage	AC 110-240V 50/60Hz, 200W
Light source	18×10W LED(4IN1)
Average lifespan	50000H
Color temperature	3200K~7200K linear adjustment
Beam angle	25°
Control mode	Multiple voice control, DMX512, built-in program self-propelled, master-slave connection mode, pixel control
Channel	8/14/26/38/74 channels(five channel modes optional)
Fixture material	Cast aluminum housing
Protection level	Fireproof V-1, protection IP65
Fixture size (L×W×H)	1060×105×165mm
Package size (L×W×H)	1100×300×220mm
Gross weight	8.5kg
Net weight	7.1kg
Working temperature	-20°C~45 °C