



# LED Flood Light

## TL-LH3406



### Description

Application: Building facades, squares, leisure sports fields, stages, billboards, rockery, building exterior lighting, landscape lighting, signs and indicative lighting, entertainment venues and stage lighting, bridges, etc.

### Features

- \*Unique appearance design, simple and natural shape.
- \*High-conductivity aluminum radiator, ventilation and convection design, smaller fixture and the larger power.
- \*Equipped with American CREE light source, high luminous flux output, good light color consistency, temperature resistance, high transparency; flame retardant optical lens can be equipped with built-in honeycomb anti-glare grille.
- \*Glue-free waterproof design, protection level IP65.
- \*Single color/RGB/RGBW four-in-one. It supports DMX512 control system. Simple wiring makes the installation and maintenance of lights more convenient and faster.
- \*Good electromagnetic compatibility, no electromagnetic interference to the surrounding environment.

### Specifications

Model	TL-LH3406
Input voltage/power	AC220V/50Hz/48W
Number of LEDs/light sources	CREE/24PCS
Beam angle	8°
Color temperature	3000K (1900, 2100, 4000, 5700K optional)
Installation method	Fixed
IP rating	IP65
Product size (L×W×H)	D180×180×233MM
Net weight	3.5KG
Certification	CE/ROHS