



Moving Head Wash Light

TL-SL155



Features

- 1 · Dimming: 0-100% electronic linear dimming with jitter-free smooth dimming technology.
- 2 · Strobe: 0-25 times per second electronic strobe with adjustable speed, built-in random strobe or pulse strobe.
- 3 · Color mixing system: RGBW (red, green, blue, white) linear color mixing; 16.8 million colors (0-100% saturation adjustable), with built-in macro function.
- 4 · Focusing: Linear motorized focusing.
- 5 · Pan/Tilt range: Pan 540° (16-bit precision scanning) with electronic error correction, Tilt 250° (16-bit precision scanning) with electronic error correction, precise scanning positioning, signal feedback, and absolute position memory.
- 6 · Display interface: Features an LCD display with 5 mechanical buttons, supports bilingual Chinese and English operating system.
- 7 · Temperature protection: Built-in NTC temperature detection function, intelligently reduces the LED output power when the LED operates over temperature.

Specification

Input voltage	AC 110-240V, 50/60Hz
Rated power	188W
Power factor	PF≥0.90
Light source	19*15W RGBW 4-in-1 LED
Average LED lifespan	50000H
Color temperature	6500K
Luminous flux	8890 lm
CRI	Ra≥70
Beam angle	8°-26°
Beam spot angle	8°-55°
Control mode	DMX512 protocol, with built-in Master-slave mode, Auto run mode, Sound-active mode, Manual control mode
Control mode	Compact mode 16CH, Standard mode 24CH
Casing material	High-temperature-resistant plastic + molded alloy + cooling method: air-cooled
Power connector	1 power input connector, 1 power output connector
Signal connector	1 DMX512 input connector, 1 DMX512 output connector
Operating temperature	-10°C ~ 45°C
IP rating	Ip20
Product dimensions (L×W×H)	309×222×366mm
Package dimensions (L×W×H)	360×260×460mm (carton)
Package gross weight	9.7kg
Product net weight	8.0kg