



Par Light

TL-SL343



Feature:

- * Strobe: independent electronic strobe 1-25Hz.
- * Electronic dimming: 0-100% independent electronic linear dimming, lifelike and flicker-free camera video, the master-slave self-propelled automatic synchronization function, and the console normally controls the self-propelled permanent synchronization.
- * LCD menu: invoke various scenes; the built-in program can be directly invoked and executed.
- * Fixture connection: three-core signal line IN/OUT and power line IN/OUT.
- * Cast aluminum housing, high luminous efficiency, uniform light mixing, stable performance; equipped with 1m hand in hand power line and signal line of 1 in and 1 out.
- * Over-temperature protection function: built-in NTC temperature control function. When the LED is overheated, the output power will be intelligently reduced.

Specifications:

Model	TL-SL343
Input voltage	AC 110-240V 50/60Hz, 200W
Light source	Ultra-bright LED 200W imported dual-color chip. A 100W warm white LED lamp bead, color temperature 3200K, and a 100W white LED
Average lifespan	50000H
Color temperature	3200K~7200K linear adjustment
Beam angle	60°
Control mode	Multiple voice control, DMX512, built-in program self-propelled, master-slave connection mode
Channel	2/6CH
Fixture material	Cast aluminum housing
Protection class	Fireproof V-1, protection IP20
Fixture size (L×W×H)	290×220×310mm
Package size (L×W×H)	250×250×360mm
Gross weight	4.1kg
Net weight	3.5kg