



# LED Flood Light

## TL-LH3763



### Description

Application: Building facades, squares, leisure sports fields, stages, billboards, rockery, building exterior lighting, landscape lighting, signs and indicative lighting, entertainment venues and stage lighting, bridges, etc.

### Features

- \*Unique appearance design, simple and natural shape.
- \*High-conductivity aluminum radiator, ventilation and convection design, smaller fixture and the larger power.
- \*Equipped with imported light source, high luminous flux output, good light color consistency, temperature resistance, high transparency; flame retardant optical lens can be equipped with built-in honeycomb anti-glare grille.
- \*Glue-free waterproof design, protection level IP65.
- \*Single color/RGB/RGBW four-in-one. It supports DMX512 control system. Simple wiring makes the installation and maintenance of lights more convenient and faster.
- \*Good electromagnetic compatibility, no electromagnetic interference to the surrounding environment.

### Specifications

Model	TL-LH3763
Input voltage/power	AC220V/50Hz/400W
Number of LEDs/light sources	CREE/216PCS
Beam angle	15° (30, 45, 60° optional)
Color temperature	RGB
Control mode	DMX512
Installation method	Fixed
IP rating	IP65
Product size (L×W×H)	650×380×318mm
Net weight	16.6KG
Certification	CE/ROHS